

KWR-600 Low-speed Wind Vane/Anemometer

The signal from the KWR-600's low-speed wind speed and direction sensor is converted using a transducer housed in the six-dot recorder, which can be set to make a continuous record of either instantaneous or 10-minute average values. The KWR-600 can also supply an external output (0-1V DC) of either instantaneous or 10-minute average values.



COMPONENTS

- 1 Low-speed wind speed/direction sensor (W632)
- 1 Wind speed/direction recorder (WR 9522-6D)
- 1 Set spare/accessory components

SPECIFICATIONS

Low-speed wind speed/direction sensor (W632)

Speed sensor	Optical pulse-type propeller
Direction sensor	Synchro-type vane
Speed accuracy	0.3 m/s at winds of 10 m/s or less 3% when winds exceed 10 m/s
Direction accuracy	±3°
Startup threshold	0.4 m/s or less
Weatherability	Winds of 90 m/s or greater
Size/weight	Approx. 250 × 509 × 700, 3.0 kg

Wind speed/direction recorder (WR 9522-6D)

Model	Six-dot
Input voltage	0 to 10 mV DC
Dot intervals	5 s (50 Hz), 4.2 s (60 Hz)
Data recorded	Wind speed: 0-20 m/s, 0-5 mV DC (inst. or avg.) Wind direction: 0-540°, 0-10 mV DC (inst. or avg.)
Drum rotation speed	25 mm/h
Chart paper	Effective width 180 mm, folded
Output	Wind speed: 0-10 m/s, 0-1 V DC (inst. or avg.) Wind direction: 0-540°, 0-1 V DC (inst. or avg.)
Power	100 V AC ±10% 50/60 Hz
Size/weight	Approx. 288 × 288 × 300, 10 kg



KOMATSU FACTORY CO.,LTD.

WEATHER INSTRUMENTS FABRICATION

1-12-13 Higashiyama Meguro-ku Tokyo 153-0043 Japan

TEL : 03-3719-7131

FAX : 03-3719-7134

e-mail : info@komatsuins.co.jp